



**Brand-Rex Optical Cables - DUP**  
Ruggedised Duplex Breakout Cable

**Product Data**

	Diameter mm	Weight kg / km	Max Tensile Load N	Min Static Bend mm	Min Dynamic Bend mm
2 Fibre	3.80 x 6.60	29	400	40 (minor axis)	60 (minor axis)

Colour Coding - Core		Colour Coding - Ruggedised Unit	
62.5/125	Blue	62.5/125	Orange
50/125	Green	50/125	Orange
OM3	Grey	OM3	Orange
OM4	Red	OM4	Orange
8/125	Yellow	8/125	Yellow

**Product Part Numbering**

	62.5/125	50/125	OM3	8/125
2 Fibre	HF 062 DUP02 L	HF 050 DUP02 L	HF OM3 DUP02 L	HF 008 DUP02 L

**Rugged Construction for Indoor, Short Run Patching**

**Easily configured into patch cords**

**Colour coded for identification**

**PRODUCT DESCRIPTION:**

The duplex fibre cable is the building block for ruggedised pigtail and patch cords. The robust construction is designed for short run indoor patching or where frequent handling is likely such as in equipment rooms, wiring closets and at user outlets.

**PRODUCT PERFORMANCE:**

Crush (N): 2000	Temp - Operation: -20°C to +60°C
Impact (Nm): 5	Temp - Storage: -20°C to +60°C
Torsion (turns / m): 5	Temp - Installation: -15°C to +60°C
Fire: IEC 60332-1	

**Fibre Selection Codes**

O62 050 H50 OM3 OM4 BM3 BM4 008 108 208

Use these part number identifiers to select the fibre type you require by replacing the fibre code in the part number e.g. HFOM3PDC24LU becomes HFBM3PDC24LU.